



**OPERATION**

Voltage is continuously applied to the input. An external isolated switch controls the timer. When closed, the ON delay (T1) begins. Upon completion, the relay energizes. When the switch opens, the OFF delay (T2) begins. Upon completion, the relay de-energizes and the cycle is complete. Reset is accomplished by reclosing the control switch after the timing cycle has completed. If the switch opens during the ON delay mode, the relay will remain de-energized and (T1) will reset. If the switch is reclosed during the OFF delay mode, the relay will remain energized and (T2) will reset. Both delay periods are independently adjustable.




**ON-Delay/OFF-Delay Relay Output**

**WIRING**



**DIMENSIONS (INCHES)**



**MODEL NUMBER**

<b>MODEL NUMBER</b>	TDJ		A			
<b>SUPPLY VOLTAGE</b>						
24 VAC or DC		24				
110/120 VAC or DC		120				
<b>TYPE OF OPERATION</b>						
Knob Adjustable				K		
Lock Nut Adjustable				L		
Fixed				F		
<b>ENCLOSURE STYLE</b>						
11-pin Round Plug-in					A	
Blade Plug-in					B	
<b>DELAY PERIOD</b>						
See page 77 for standard ranges available						

Example: TDJ-120-ALA-300—Delay on Operate/Delay on Release, 120 Volts AC or DC, lock nut adjustable from 3 to 300 seconds, 11-pin octal plug-in, UL recognized.

**SPECIFICATIONS**

**TIMING RANGES**

Virtually unlimited. See page 77 for standard ranges available.

**OUTPUT RATING** DPDT, 10 A @ 250 VAC or 24 VDC, resistive; 211 VA @ 120 VAC, inductive

**TIMING** Minimum Setting +0 – 20%

**TOLERANCES** Maximum Setting ±10%;

**REPEATABILITY** 1% maximum; no first cycle effect

**RESET TIMES** Before Time Out 100 mSEC  
After Time Out 50 mSEC

**RECYCLE TIME** 40 mSEC

**SUPPLY VOLTAGE** 24 or 120 VAC or VDC, 50/60 Hz; ±10%

**FALSE TRANSFER** No

**REVERSE POLARITY PROTECTED** Yes

**POWER CONSUMPTION** 3 watts (approximately)

**DUTY CYCLE** Continuous

**TEMPERATURE RATING** Operate 32° to 131°F (0° to +55°C)  
Storage -49° to 185°F (-45° to +85°C)

**LIFE EXPECTANCY** Mechanical 10 million operations (minimum)  
Electrical 100,000 operations @ rated load

**WEIGHT** 6.4 oz.

### STANDARD DELAY RANGES AVAILABLE

The chart below shows the standard adjustable time delay ranges available. The part number suffix equals the maximum adjustable delay period of the timer. No letters following the suffix number indicates the delay period in seconds; an M indicates minutes; and an H indicates hours.

### STANDARD DELAY RANGE CHART

PART NUMBER SUFFIX	MINIMUM SETTING	MAXIMUM SETTING
010	0.1 seconds	10 seconds
030	0.3 seconds	30 seconds
060	0.6 seconds	60 seconds
100	1 second	100 seconds
200	2 seconds	200 seconds
300	3 seconds	300 seconds
600	6 seconds	600 seconds
900	9 seconds	900 seconds
30M	18 seconds	30 minutes
60M	36 seconds	60 minutes
90M	54 seconds	90 minutes
2H	1.2 Minutes	2 hours
4H	2.4 Minutes	4 hours
8H	4.8 Minutes	8 hours
12H	7.2 Minutes	12 hours
16H	9.6 Minutes	16 hours
20H	12 Minutes	20 hours
24H	14.4 Minutes	24 hours

Longer delays available upon request. Consult Factory

### EXTERNAL RESISTANCE SELECTION

On models specified as having the external resistor adjustability feature, the delay period is set by placing resistance across designated pins or terminals. One meg ohm resistance provides the maximum delay on all models. The minimum delay is obtained by jumping the terminals together.

The resistor or potentiometer chosen should be a 1/4 watt or larger.

To determine the resistor value required for a specific time delay, use the following formula:

$$R_{ext} = (T_{des}/T_{max}) \times 1000$$

$R_{ext}$  = Resistance value required to obtain  $T_{des}$  (in K ohms)

$T_{des}$  = Desired time delay

$T_{max}$  = Maximum delay period of the timer

Example: Model TDC-120-ARC-300; find the external resistance value required for a 240 second delay:

$$R_{ext} = \frac{240}{300} \times 1000 = 800 \text{ K ohms}$$

### “FIXED” DELAY OPTION

Most ATC Diversified timers are available with the delay period factory preset (“fixed”) for some specified duration. When this option is ordered, the part number should have an “F” in the Type of Operation designation: and the last digits should specify the desired time delay in seconds (S), minutes (M), or hours (H).

Example: TDC 120-AFA-30M—delay-on-operate, 120 Volts AC or DC, 8-pin octal plug-in package with a 30 minute fixed delay.

### OFF/ON DELAY TIMERS

Included in ATC Diversified’s broad line of timers are six (6) models that feature independent OFF/ON delay adjustments. They are TDF, TDH, TDI, TSF, and TSH. Notice in the ordering information section on each of their respective pages the timing range is specified by a three (3) digit suffix. This indicates that both the OFF and ON delay periods have the same timing ranges. Example: TDF-120-ALA-300: Both OFF and ON delay periods are independently adjustable from 3 to 300 seconds.

In the event that two (2) separate delay ranges would be required, the part number is modified to add a slash (/) followed by three (3) more digits. Since the OFF delay (TI) is first in all models, it is specified first in the part number. Example: TDF-120-ALA-12H/30M: the OFF delay is adjustable from 7.2 minutes to 12 hours and the ON delay is adjustable from 18 seconds to 30 minutes.

NOTE: Combinations of various “types of operation” are available: fixed/adjustable, knob/lock nut, etc. Consult factory.

### MODEL NUMBER

<b>MODEL NUMBER</b>	T						
<b>TIME DELAY</b>							
<b>SERIES</b>							
Relay Output	D,U						
Solid State Output	S						
<b>MODE OF OPERATION</b>							
<b>SUPPLY VOLTAGE</b>							
24 Volts		24					
120 Volts		120					
240 Volts		240					
<b>TYPE OF VOLTAGE</b>							
AC			A				
DC			D				
<b>TYPE OF OPERATION</b>							
Knob Adjustment				K			
Lock Nut Adjustment				L			
Fixed (Factory Preset)				F			
External Resistor Adjustable				R			
<b>ENCLOSURE STYLE</b>							
8 or 11-pin Round Plug-in					A		
Blade Plug-in					B		
Potted Cube					C		
<b>DELAY PERIOD</b>							
See Standard Delay Range Chart							

NOTE: Not all time delays are available with each option shown above. The specific options for each timer type are described on their respective pages.