

P350 Filter

Excellent Filtration

The element is made from high efficiency glass microfiber with high grade 316SS end caps.

Stainless Steel Filter complies with NACE MR0175 for sulfide stress cracking resistant metallic material for oil field equipment.

Maintenance

A tight seal is guaranteed by the use of a thread element connection. The filter housing and element have been polished and degreased. No special lubricants are needed in the field for replacing the element.

The element is threaded into the housing so there is no need for extra parts during installation or maintenance of the filter. There is no chance of losing top or bottom seals or rings required for installation.

Applications

- Filtering Supply Gas
- Filtering Air Supply

P350 Part Matrix

P3500200000			
	↑	↑	↑
	P		Drain Option
	V		Drain Plug
			Manual Drain Valve
			Filter Option
	25		
	01		1 Micron
	05		5 Micron
	50		50 Micron
			Material
	0		Stainless Steel
	1		Aluminum

P350 Replacement Filter Elements

25 Micron	971-350-000
1 Micron	971-350-001
5 Micron	971-350-002
50 Micron	971-350-003

Flow Rates

Body Size	Pressure Differential	SCFM
1/4 NPT	5 PSIG	19 SCFM
	10 PSIG	27 SCFM
	20 PSIG	40 SCFM

Specifications

Body Size	1/4 NPT	
Max Operating Pressure	Aluminum	2150 PSIG
	Stainless Steel	5000 PSIG
Max Operating Temperature	248° F	120° C
Drain Valve Assemble Options	Plugged Drain Port Manual Drain Valve	
Weight Approximate		
Aluminum	0.5 lb	0.22 kg
Stainless Steel	1.1 lb	0.5 kg
Materials of Construction		
Body,	Stainless Steel (NACE) Construction or Aluminum	
Filter	25 Micron Glass Microfiber (Standard) Stainless Filter End Caps	



P350 Dimensions

